

Harlequin 2500LT Blue Station



Tank Dimensions:

Diameter: 2090mm

Height: 1930mm

Brimful Capacity: 2716Litres

Nominal Capacity: 2580Litres

Weight: 200kg

Material: Medium density polyethylene

Standard Equipment

- 35L/min pump
- Digital flow meter ($\pm 1\%$)
- 6m length, $\frac{3}{4}$ " fuel delivery hose
- Stainless steel auto delivery nozzle
- 2" dry break coupling
- 1" suction hose with check valve and 80 micron strainer
- Local and remote contents gauge
- LRC overfill prevention device
- Bulkhead light
- Lockable door

Optional Equipment at Additional Cost

1. **Arctic Pack**
Insulated inner tank and thermostatically controlled heat trace system
2. **Ventilation Pack**
Thermostatically controlled cooling fans and outer tank vents

Note:

- This tank is only suitable for the storage and dispensing of AdBlue SCR Urea.

Installation

- This tank should be situated on a level base that is 300mm greater than the maximum dimensions of the tank on all sides.
- It is recommended this tank be placed in a shaded position and protected from direct sunlight.
- The electrical system may have a minimum current rating of 13amps. It is recommended that 15amp 1.5mm² core cable be used. A Residual current device should be incorporated. All electrical installation work must be undertaken by a registered electrician.

Issued By:

Clarehill Plastics Ltd, 21 Clarehill Road, Moira, N.Ireland, BT67 0PB.

T: +44 (0)28 92611077 F: +44 (0)28 92612672 E: info@harlequinplastics.co.uk

W: www.harlequinplastics.co.uk